	Application No.	Applicant(s)	
<b>'</b>			
Madiaa af Allassa bilida	09/886,550 Examiner	CLARK ET AL.  Art Unit	
•			
	Hien D. Vu	2833	
The MAILING DATE of this communication appea All claims being allowable, PROSECUTION ON THE MERITS IS (Concrewith (or previously mailed), a Notice of Allowance (PTOL-85) of NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIGHT of the Office or upon petition by the applicant. See 37 CFR 1.313 and the Office of the Office	OR REMAINS) CLOSED in to other appropriate commune GHTS. This application is su	his application. If not included ication will be mailed in due course. T	
. 🔀 This communication is responsive to the communication on	<u>2/1/06</u> .		
2. ☑ The allowed claim(s) is/are <u>74 and 82-85</u> .			
3. Acknowledgment is made of a claim for foreign priority und	ler 35 U.S.C. § 119(a)-(d) or	<b>(f)</b> .	
a) 🗌 All b) 🔲 Some* c) 🔲 None of the:			
<ol> <li>Certified copies of the priority documents have to</li> </ol>	been received.		
<ol><li>Certified copies of the priority documents have to</li></ol>	been received in Application	No	
<ol><li>Copies of the certified copies of the priority docu</li></ol>	uments have been received	n this national stage application from	the
International Bureau (PCT Rule 17.2(a)).			
* Certified copies not received:			
Applicant has THREE MONTHS FROM THE "MAILING DATE" of noted below. Failure to timely comply will result in ABANDONME THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.		reply complying with the requirement	S
<ol> <li>A SUBSTITUTE OATH OR DECLARATION must be submitt INFORMAL PATENT APPLICATION (PTO-152) which gives</li> </ol>			F
5. CORRECTED DRAWINGS ( as "replacement sheets") must	be submitted.		
(a) $\square$ including changes required by the Notice of Draftsperso	n's Patent Drawing Review	(PTO-948) attached	
1) 🗌 hereto or 2) 🗍 to Paper No./Mail Date			
(b) ☐ including changes required by the attached Examiner's a Paper No./Mail Date	Amendment / Comment or in	n the Office action of	
Identifying indicia such as the application number (see 37 CFR 1.8 each sheet. Replacement sheet(s) should be labeled as such in the	(4(c)) should be written on the a header according to 37 CFR	drawings in the front (not the back) of 1.121(d).	
<ol> <li>DEPOSIT OF and/or INFORMATION about the deposi attached Examiner's comment regarding REQUIREMENT For</li> </ol>			
Attachment(s)  I.   Notice of References Cited (PTO-892)	5. □ Notice of Info	rmal Patent Application (PTO 152)	
. ☐ Notice of Praftperson's Patent Drawing Review (PTO-948)		rmal Patent Application (PTO-152)	
. Information Disclosure Statements (PTO-1449 or PTO/SB/08)	Paper No./M	ail Date <u>2/2/06</u> . mendment/Comment	
Paper No./Mail Date  Examiner's Comment Regarding Requirement for Deposit		tatement of Reasons for Allowance	
of Biological Material		i	
	9.	Hin Un	
		HIENVU PRIMARY EXAMINER	1

Art Unit: 2833

## **EXAMINER'S AMENDMENT**

An examiner's amendment to the record appears below. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.

Authorization for this examiner's amendment was given in a telephone interview with Mr. Frank Carroll on 2/1/06.

The application has been amended as follows:

In the specification:

Page 1, lines 3-4 "This application is ... April 17,1998." have been changed to -This application is a continuation of United States application no. 09/160,900, filed
September 25, 1998, now U.S. patent no. 6,319,075, which claims the benefit of United
States provisional application no. 60/082,091, filed April 17, 1998, all of which are
incorporated herein by reference.

In the claims:

- 74. (currently amended) An electrical connector for power applications, the connector comprising:
  - a) an insulative housing;
- b) a cavity disposed in said insulative housing, the cavity defined by a first wall and two spaced apart housing walls that each extend from the first wall; and
- c) a power contact disposed in said cavity, said power contact comprising: a pair of opposed contact walls defined by a first planar panel, a second planar panel, a bridging element adjoining the first and second planar panels, a medial space between the first planar panel and the second planar panel; a first compressible beam that adjoins the first planar panel and extends in a direction generally parallel to one of said two spaced apart housing walls; a second compressible beam that adjoins the second planar panel and extends in a direction generally parallel to one of said two spaced

Application/Control Number: 09/886,550 Page 3

Art Unit: 2833

apart housing walls, the first and second compressible beams extending outwardly away from each other and inwardly toward each other; and separated contact terminals that extend from the first planar panel and the second planar panel in a direction perpendicular to the first compressible beam and the second compressible beam and generally parallel to one of said two spaced apart housing walls,

wherein at least one <u>portion</u> of the first planar panel and the second planar panel is spaced from an adjacent one of said housing walls such that heat dissipation can also occur from an exterior surface of the power contact.

75-81. (canceled)

- 82. (currently amended) The electrical connector of claim 74, wherein [[said]] <u>a</u> heat dissipation channel <u>defined by one of the first and second planar panels and the adjacent one of the housing walls</u> is fluidly connected to [[said]] <u>a</u> heat dissipation through-hole <u>defined by the housing</u>.
- 83. (currently amended) The electrical connector of claim 74, further comprising a lateral positioning element for spacing one of the first and second planar panels from one of the of the two spaced apart housing walls.
- 84. (previously presented) The electrical connector of claim 83, wherein said lateral positioning element extends from one of said two spaced apart walls.
- 85. (currently amended) A connector system, comprising:
  - (A) a connector, comprising:
    - a) an insulative housing;
- b) a plurality of cavities disposed in said insulative housing defined by a series of housing walls; and
- c) a power contact disposed in each one of said plurality of cavities, said power contact comprising a pair of opposed contact walls defined by a first planar

Art Unit: 2833

panel, a second planar panel, a medial space between the first planar panel and the second planar panel, a first flexible beam extending from the first planar panel, and a second flexible beam extending from the second planar panel, the first and second flexible beams extending outwardly away from each other and inwardly toward each other;

wherein heat dissipation can occur from interior contact surfaces by passage of air in the medial space; and

wherein at least one <u>portion</u> of the first planar panel and the second planar panel is spaced from an adjacent housing wall such that heat dissipation can also occur from an exterior contact surface; and

- (B) a mating connector, comprising:
  - a) an insulative housing;
- b) a plurality of cavities disposed in said insulative housing of the mating connector, the cavities being defined by a series of housing walls; and
- c) a plurality of receptacle contacts for receiving the first and second flexible beams of respective ones of the power contacts, each of the receptacle contacts being disposed in a respective one of said plurality of cavities disposed in said insulative housing of the mating connector, each of said receptacle contacts comprising a pair of opposed contact walls defined by a first planar panel, a second planar panel, and a medial space between the first planar panel and the second planar panel of the receptacle contact, each of said receptacle contacts further comprising a bridging element adjoining the first and second planar panels of the receptacle contact;

wherein heat dissipation can occur from interior contact surfaces of the receptacle contacts by passage of air in the medial spaces of the receptacle contacts; and

wherein at least one <u>portion</u> of the first planar panel and the second planar panel of each of the receptacle contacts is spaced from an adjacent housing wall of the mating connector such that heat dissipation can also occur from an exterior contact surface of the receptacle contact.

86. (canceled)

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Hien D. Vu whose telephone number is 571-272-2016. The examiner can normally be reached on 9-5.

HIEN VU PRIMARY EXAMINER

Him Un

HV 2/2/06